

YÜK MAKARASI / PULLEY BLOCKS**NL-HPB 10****NL-HPB 20****NL-HPB 32****NL-HPB 64**

| | | 1000 | 2000 | 3200 | 6400 | |
|-------------------------------------|----------------|-------------|-------------|-------------|-------------|----|
| Çalışma yükü / Working load | | | | | | kg |
| Mandal açıklığı / Hook hatch | | 23 | 27 | 31 | 42 | mm |
| Halat ölçüsü / Rope diameter | | Ø7 | Ø13 | Ø15 | Ø18 | mm |
| Ölçüler / Dimensions | B | 118 | 199 | 230 | 270 | mm |
| | B ₁ | 76 | 92 | 108 | 116 | mm |
| | B ₂ | 17 | 24 | 28 | 35 | mm |
| | C | 23 | 27 | 31 | 42 | mm |
| | D ₁ | 85 | 150 | 180 | 210 | mm |
| | D ₂ | 105 | 190 | 220 | 260 | mm |
| | L | 305 | 425 | 496 | 655 | mm |
| | L ₁ | 200 | 263 | 295 | 375 | mm |
| | L ₂ | 23 | 30 | 40 | 47 | mm |
| | R | 4 | 7 | 9 | 10 | mm |
| Ağırlık / Weight | | 3.3 | 8.9 | 15.5 | 26.5 | kg |

- Netlift yük makaralarının bir yüzü halatın bobine rahat yerleştirilebilmesi için açılabilir.
- Kancanın çekim yönüne hareketi kasnak bloğunu güvenli bir şekilde kilitleyebilir.
- Yüksek kaliteli çelikten imal edilmiş bobinlerin yivleri özel makinalarda açılmıştır.
- prEN13157:2003 ve Machinery Directive 2006/ 42 EC'ye göre imal edilmiştir.

- One side of the NETLIFT pulley blocks is hinged and can be opened for easy and quick positioning of the rope on the sheave.
- Swinging the hook in the direction of pull securely locks the pulley block.
- The high quality cast steel sheaves have machined grooves
- Manufactured according to prEN 13157:2003, machinery directive 2006/ 42 EC

Art.No. 52000079

NL-HPB 10

Art.No. 52000080

NL-HPB 20

Art.No. 52000081

NL-HPB 32

Art.No. 52000082

NL-HPB 64